




Heat-resistant cables - H05G-K/H07G-K



Technical attributes

Standards	DIN VE 0282-7
Conductor material	Cu, tinned
Conductor category	5
Core insulation	rubber (CR) EM5
Outer sheath colour	black
Temperature range min., mobile operation	-25 °C
Temperature range max., mobile operation	+110 °C
Temperature range min., fixed installation	-25 °C
Temperature range max., fixed installation	+110 °C
Nominal voltage U ₀ /U	450/750 V

Product table

product number	product name	Weight ca. [kg]	Cu-weight [kg_km]	Outer-Ø ca. [mm]	Outer sheath colour
00921004	H05G-K 0,75 sw	11,00	7,20	2,30	black
00921014	H05G-K 1 sw	16,00	9,60	2,80	black
00921002	H07G-K 1,5 sw	25,00	14,40	3,00	black
00921010	H07G-K 1,5 bl RAL5015	25,00	14,40	3,00	RAL 5015 blue
00921011	H07G-K 1,5 gn / ge	25,00	14,40	3,00	green/yellow
00921003	H07G-K 2,5 sw	32,00	24,00	3,70	black
00921016	H07G-K 2,5 gn / ge	32,00	24,00	3,70	green/yellow
00921008	H07G-K 4 sw	49,00	38,00	4,60	black
00921018	H07G-K 4 gn / ge	49,00	38,00	4,60	green/yellow
00921009	H07G-K 6 sw	69,00	58,00	5,20	black
00921001	H07G-K 10 sw	115,00	96,00	6,60	black
00921015	H07G-K 16 sw	180,00	154,00	8,10	black
00921017	H07G-K 16 gn / ge	180,00	154,00	8,10	green/yellow
00921005	H07G-K 25 sw	275,00	240,00	9,70	black
00921006	H07G-K 35 sw	365,00	336,00	11,00	black
00921007	H07G-K 50 sw	530,00	480,00	13,00	black
00921013	H07G-K 70 sw	720,00	672,00	14,50	black
00921012	H07G-K 95 sw	940,00	912,00	17,00	black