



Halogen-free cables - JE-H(ST)HQH E90 steel wire braid



Technical attributes

Standards	DIN VDE 0815
Conductor type	cable conductors blanc (0,8 mm/0,5 mm ²)
Core colours	DIN VDE 0815
Outer sheath	halogen-free special mixture
Outer sheath colour	red
Temperature range min., mobile operation	-5 °C
Temperature range max., mobile operation	+50 °C
Temperature range min., fixed installation	-30 °C
Temperature range max., fixed installation	+70 °C
Nominal voltage U ₀ /U	225 V
Test voltage	Core/core = 500, core/screen = 2000 V
halogen-free	
RoHS-compliant	yes

Note

steel wire braid

Product table

product number	product name	halogen-free	Weight ca. [kg]	Cu-weight [kg_km]	Outer-Ø ca. [mm]	Outer sheath colour
01615001	JE-H(ST)HQH E90 2x2x0,8 BMK		152,00	25,00	10,40	red
01615002	JE-H(ST)HQH E90 4x2x0,8 BMK		277,00	45,00	14,70	red
01615003	JE-H(ST)HQH E90 8x2x0,8 BMK		544,00	85,00	21,20	red
01615004	JE-H(ST)HQH E90 12x2x0,8 BMK		600,00	126,00	22,80	red
01615005	JE-H(ST)HQH E90 16x2x0,8 BMK		696,00	166,00	23,20	red
01615006	JE-H(ST)HQH E90 20x2x0,8 BMK		868,00	206,00	26,90	red
01615007	JE-H(ST)HQH E90 32x2x0,8 BMK		1359,00	327,00	34,60	red
01615008	JE-H(ST)HQH E90 40x2x0,8 BMK		1798,00	407,00	40,60	red
01615009	JE-H(ST)HQH E90 52x2x0,8 BMK		2040,00	527,00	43,70	red