



## Installation cables - NYIF-O/J tape conduit



### Technical attributes

Standards	DIN VDE 0250-201
Conductor type	solid copper conductor
Conductor standard	DIN VDE 0295
Conductor category	1
Core colours	DIN VDE 0293
Outer sheath	vulcanized rubber compound
Outer sheath colour	grey
Nominal voltage U <sub>0</sub> /U	0,23/0,4 kV
RoHS-compliant	yes

### Description

For fixed installation in dry rooms and plaster. Installation in cavities of concrete, stone or non-combustible materials is permitted.

### Note

tape conduit

### Product table

product number	product name	Weight ca. [kg]	Cu-weight [kg_km]	Outer-Ø ca. [mm]	Outer sheath colour
01704001	NYIF-O 2 x 1,5	75,00	29,00	12,00	grey
01704002	NYIF-J 3 x 1,5	111,00	43,00	19,00	grey
01704003	NYIF-O 3 x 1,5	111,00	43,00	19,00	grey
01704004	NYIF-J 4 x 1,5	151,00	58,00	26,00	grey
01704005	NYIF-J 5 x 1,5	191,00	72,00	33,00	grey
01704006	NYIF-J 3 x 2,5	148,00	72,00	21,50	grey
01704007	NYIF-J 5 x 2,5	249,00	120,00	37,00	grey