



Round cables with suspension element - STCN (EMC-type) Neoprene control cables with suspension element



Technical attributes

According to DIN VDE 0250 part 807 and DIN Standards

VDE 0282 part 807 and 808

Conductor material Cu. bare

cable blanc, fine stranded Conductor type

Conductor standard **DIN VDE 0295** Conductor category

Core structure stranded

Core colours with DIN VDE 0293 to 5-wire colour, from

6-wire bk with follow with numbers printed ,

protective conductor gn/ye

Outer sheath Outer sheath colour Polychloroprene

black -30 °C Temperature range min., mobile

operation Temperature range max., mobile +70 °C

operation

Temperature range min., fixed -40 °C

installation

Temperature range max., fixed +70 °C

installation 450/750 V Nominal voltage Uo/U Test voltage Minimum bending radius mobile 3000 V

operation

suspension element

RoHS-compliant yes

Description

As the elevator control cable, as a control line on conveyors, machine tools or measuring and signal cable for medium mechanical stress in dry, damp and wet rooms and outdoors, where a high resistance to oils, greases and chemical attack is required. Also for fixed installation on plaster or machine parts. Suspension height max. 80 m with respect to the tensile strength

10 x cable-Ø

Note

Neoprene control cables with suspension element

Product table

product number	product name	Weight ca. [kg]	Cu-weight [kg_km]	Outer-Ø ca. [mm]	Outer sheath colour
00602001	STCN-JZ 6 x 0,5	180,00	80,70	11,50	black
00602012	STCN-OZ 6 x 0,5	180,00	80,70	11,50	black
00602002	STCN-OZ 6 x 0,75	205,00	80,70	12,00	black
00602003	STCN-JB 4 x 1,0	185,00	74,00	11,50	black
00602004	STCN-JZ 7 x 1,0	300,00	187,50	15,00	black
00602005	STCN-JZ 12 x 1,0	545,00	201,20	20,50	black
00602007	STCN-JZ 18 x 1,0	630,00	287,50	21,00	black
00602008	STCN-IZ 24 × 1.0	900.00	394.80	25.00	black

Stand 08.09.2021 no limit or warranty. 1/2





Round cables with suspension element - STCN (EMC-type) Neoprene control cables with suspension element

product number	product name	Weight ca. [kg]	Cu-weight [kg_km]	Outer-Ø ca. [mm]	Outer sheath colour
00602006	STCN-JZ 6 x 1,5	430,00	126,00	15,00	black

