



Industrial PVC-cables - X03VH-H/N03VH-H



Technical attributes

Standards	DIN VDE 0281
Conductor material	Cu, bare
Conductor type	Cu-bare
Conductor standard	DIN VDE 0295
Conductor category	5
Outer sheath	PVC
Outer sheath colour	black / white or upon request
Temperature range min., mobile operation	+5 °C
Temperature range max., mobile operation	+70 °C
Nominal voltage U ₀ /U	300/300 V
Test voltage	2000 V
RoHS-compliant	yes

Description

For use on lightweight hand-held devices with low mechanical stress, as well as for connecting light electrical appliances such as kitchen appliances, office equipment and radios, but not approved for cooking, heating, and heating equipment and commercial for outdoor use in commercial and agricultural businesses and to connect power tools used

Product table

product number	product name	Weight ca. [kg]	Cu-weight [kg_km]	Outer-Ø ca. [mm]	Outer sheath colour
01805001	X03VH-H 2 x 0,75 bk RAL 9005	27,00	14,40	7,20	RAL 9005 black
01805002	X03VH-H 2 x 0,75 bn RAL 8014	27,00	14,40	7,20	brown
01805003	X03VH-H 2 x 0,75 wh RAL 9010	27,00	14,40	7,20	RAL 9010 white