



Installation cables - YR bell cable



Technical attributes

Conductor material	Cu, bare
Conductor type	solid
Conductor standard	DIN VDE 0295
Conductor category	1
Outer sheath	PVC
Outer sheath colour	white
Temperature range min., mobile operation	-5 °C
Temperature range max., mobile operation	+50 °C
Temperature range min., fixed installation	-5 °C
Temperature range max., fixed installation	+50 °C
working peak voltage	100 V
RoHS-compliant	yes

Description

for fixed wiring to installation cable on and unter plaster

Note

bell cable

Product table

product number	product name	Weight ca. [kg]	Cu-weight [kg_km]	Outer-Ø ca. [mm]	Outer sheath colour
01706001	YR 2 x 0,8 wh	25,00	9,60	4,00	white
01706002	YR 3 x 0,8 wh	32,00	14,40	4,40	white
01706003	YR 4 x 0,8 wh	40,00	19,20	4,90	white
01706004	YR 5 x 0,8 wh	50,00	24,00	5,40	white
01706005	YR 6 x 0,8 wh	58,00	28,80	5,80	white
01706006	YR 8 x 0,8 wh	75,00	38,00	6,50	white
01706007	YR 10 x 0,8 wh	98,00	48,00	7,60	white
01706008	YR 12 x 0,8 wh	106,00	58,00	7,70	white
01706009	YR 14 x 0,8 wh	122,00	67,00	8,20	white
01706010	YR 16 x 0,8 wh	136,00	77,00	8,60	white
01706011	YR 20 x 0,8 wh	170,00	96,00	9,10	white
01706012	YR 24 x 0,8 wh	198,00	115,00	10,50	white