

AES/EBU & DMX 110 ohm



DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

Application: Flexible cable for transmission of audio signals with low attenuation.

Construction and technical data:

Conductor material:	copper, bare
Conductor construction:	Class 5 = flexible
Insulation:	polyethylene
Screen:	copper braid
Sheathing material:	PVC
Permitted outer cable temperature, fixed, °C:	-30 - +70 °C



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

Cross section	2x0.34	4x0.34
Capacitance core/core (pF/m)		< 65
Capacitance core/screen (pF/m S)	115	245
Screen coverage (%)	95	85
Insulation resistance (GOhm x km)	> 10	> 5
Core colours	wh + rd	wh + bn, gn + ye

AES/EBU & DMX 110 ohm

Protective conductor: no

part no.	part name	RI [Ohm/km]	Ø [mm]	Cu	G [kg]
033831	(2X0.34)StDY BK	57	6.6	10.2	50
033833	(4X0.34)StCY BK	57	7.2	33	65

RI	Conductor resistance
Ø	outer diameter approx.
Cu	Copper weight (GER)
G	net weight per 1000