

Compensation cable

AGL type KCA LiY(St)Y



DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

Application: For connecting thermo elements to measuring electronics.

Construction and technical data:

Specification/Standard:	DIN IEC 584
Conductor material:	Ni/CrNi
Insulation:	PVC
Screen:	plastic coated aluminium foil + solid copper drain wire
Sheathing material:	PVC
Insulation/sheath colour:	gn(+)-wh(-)/gn
Flame-retardant:	VDE 0482-332-1-2/IEC 60332-1-2
Operating temperature:	0 - 150 °C
Permitted outer cable temperature, fixed, °C:	-5 - +70 °C
Permitted outer cable temperature, moved, °C:	0 - 70 °C
Class:	2 (+/- 2,5 °C)



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

AGL type KCA LiY(St)Y

Test voltage: 1 kV

part no.	part name	Ø [mm]	G [kg]
070886	LiY(St)Y 02X1.5 NiCr/Ni WH/GN colour code acc. to IEC, type K	7.3	76

Ø | outer diameter approx.

G | net weight per 1000