

LAN cable

FABER[®] Industrial dataline 200 flex PUR



Application: For connection of IT system units in the desktop and distribution area in industrial environments (INDUSTRIAL ETHERNET). For use in dry and wet rooms as well as temporary outdoors under medium mechanical stress. The AWG 26 version may be connected with RJ 45 plugs.

Construction and technical data:

Standard:	UL/CSA
Specification/Standard:	ISO/IEC 11801, EN 50173, UL/CSA
Conductor material:	copper, bare
Conductor construction:	Class 5 = flexible
Insulation:	foam skin
Screen:	aluminium foil + tinned copper braid
Sheathing material:	polyurethan
Flame-retardant:	VDE 0482-332-1-2/IEC 60332-1-2
Permitted outer cable temperature, fixed, °C:	-40 - +80 °C
Bending radius, fixed installation:	8 x Ø
Bending radius, moving application:	12 x Ø
Impedance:	100 Ohm
Velocity factor (NVP):	0.75 v/c
Category:	5e



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

FABER[®] Industrial dataline 200 flex P

Maximum operating capacity:	48 nF/km
Test voltage:	0.7 kV
Core identification:	colours acc. to IEC 60708

part no.	part name	Ø [mm]	Cu	G [kg]
101307	Faber [®] Industrial Dataline 200 Flex SFTP PUR cat.5e 4X2XAWG26/7 FRNC cUL blue, similar to RAL 5021	6.4	25	54
101310	Faber [®] Industrial Dataline 200 Inst. SFTP PUR cat.5e 2X2XAWG26/7 FRNC cUL green, similar to RAL 6018	5.7	20	43

∅	outer diameter approx.
Cu	Copper weight (GER)
G	net weight per 1000