

Profi-bus cable

Profibus DP FPE/CAM/TCWB/PVC/SWA/LSZH

with anti-rodent protection

DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

Application: Profibus is an international fieldbus-standard for universal application in production and process automation. For fixed installation indoors, outdoors and in the ground.

Construction and technical data:

Conductor material:	copper, bare
Conductor construction:	solid
Insulation:	foam-PE
Stranding unit:	Pair
Material inner sheath:	PVC
Screen:	aluminium foil + tinned copper braid
Armour:	round steel wire, galvanized
Sheathing material:	halogen-free
Colour of outer sheath:	black
UV-resistant:	yes



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

Profibus DP FPE/CAM/TCWB/PVC/SWA/LSZH with anti-rodent protection

Loop resistance:	110 Ohm/km
Core identification:	red, green
peak operating voltage, V:	250 V

part no.	part name	Ø [mm]	Cu	G [kg]
101690	Profibus L2/FIP/DP/FMS Insta. LSZH FPE/CAM/TCWB/PVC/SWA/LSZH 01X2X0,64 BK ** please note the application **	12.4	34	290

Ø	outer diameter approx.
Cu	Copper weight (GER)
G	net weight per 1000