

PUR insulated cable

S07BQ-F




Application: In dry and wet environments as well as temporary outdoors under medium mechanical stress. For connection of electrical tools on building sites or in cold environments. The cable is highly oil-, abrasion- and impact resistant.

Construction and technical data:

Conductor - acc. to EN60228
Insulation - acc. to EN 50363-1
Inner Sheath - thickness 1.7 mm
Outer sheath - TPU - acc. to EN 50363-10-2

Standard:	DIN EN 50525-2-21 (VDE 0285-525-2-21)
Conductor material:	copper, bare
Conductor construction:	Class 5 = flexible
Insulation:	rubber EI7
Material inner sheath:	elastomer
Sheathing material:	polyurethan
Colour of outer sheath:	black
Flame-retardant:	EN 60332-1-2
UV-resistant:	yes
Max. temperature at conductor, °C:	90 °C
Max. short circuit temperature at conductor, °C:	250 °C
Permitted outer cable temperature, fixed, °C:	-40 - +80 °C
Permitted outer cable temperature, moved, °C:	-25 - +80 °C
Bending radius, fixed installation:	4 x Ø
Bending radius, moving application:	12 x Ø



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

S07BQ-F

Nominal voltage U_o: 450 V

Nominal voltage U: 750 V

Test voltage: 2 kV

Core identification: green-yellow + numbers

part no.	part name	DI [mm]	RI [Ohm/km]	Wi [mm]	I _{bl} [A]	W _m [mm]	Ø [mm]	Cu	G [kg]
053444	S07BQ-F 36G2.5 UV-Bestaendig BK	0.26	7.98	0.9	27	2.6	41.8	864	1800

DI | diameter conductor

RI | Conductor resistance

Wi | Insulation wall thickness

I_{bl} | Ampacity in air (30 °C)

W_m | Wall thickness of sheath

Ø | outer diameter approx.

Cu | Copper weight (GER)

G | net weight per 1000