

Medium voltage reeling cable

URSUS[®] MT KN PLUS



Application: Flexible medium voltage reeling cable with reduced weight and dimensions, for high and extreme mechanical stress, e.g. torsional stress, deflection and high reeling speed. Other applications have to be agreed with Faber otherwise warranty may become void.

- Min. bending radius: acc. to VDE 0298-3
- Max. current rating: acc. to VDE 0298-4

Remark on REACH: The following substances from the REACH candidate list are used for all products on this datasheet with a proportion of more than 0.1 %: CAS 85535-85-9

Construction and technical data:

Standard:	DIN VDE 0250-813 (with ref. to)
Conductor material:	tinned copper
Conductor construction:	Class 5 = flexible
Insulation:	rubber 3GI3
Electrical field control:	inner and outer semiconducting rubber layer
Central filler:	semiconductive compound on Kevlar [®] element
Core wrapping:	semiconductive tape
Arrangement of protective conductors:	split in the outer interstices
Material inner sheath:	rubber Gm1b/5GM5
Torsion protection:	polyester braid
Torsion:	+/- 25 °/m
Sheathing material:	rubber (CR) 5GM5
Colour of outer sheath:	red
Flame-retardant:	VDE 0482-332-1-2/IEC 60332-1-2
UV-resistant:	yes
Oil-resistant:	EN 60811-404
Ozone-resistant:	yes
Max. temperature at conductor, °C:	90 °C
Max. short circuit temperature at conductor, °C:	250 °C
°C:	
Permitted outer cable temperature, fixed, °C:	-50 - +80 °C
Permitted outer cable temperature, moved, °C:	-30 - +80 °C
Maximum tensile strength at the conductor:	30 N/mm ²
Operating speed:	240 m/min.



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

Max. tensile strength 3xphase + center element

nominal cross-section conductor	25 mm ²	35 mm ²	50 mm ²
Max. tensile strength	6250 N	7150 N	8500 N

URSUS[®] MT KN PLUS 3.6/6 kV

Nominal voltage U₀: 3.6 kV

Nominal voltage U: 6 kV

Maximum permitted operating voltage in 7.2 kV

three-phase systems:

Test voltage: 11 kV

part no.	part name	RI [Ohm/km]	Ø [mm]	Cu	G [kg]
052594	3X25 + 3X25/3	0.795	40.3	960	2380
052595	3X35 + 3X25/3	0.565	44.6	1248	2920
052596	3X50 + 3X25/3	0.393	47.7	1680	3520
053790	3X95 + 3X50/3	0.21	59.6	3216	5640

URSUS[®] MT KN PLUS 6/10kV

Nominal voltage U₀: 6 kV

Nominal voltage U: 10 kV

Maximum permitted operating voltage in 12 kV

three-phase systems:

Test voltage: 17 kV

part no.	part name	RI [Ohm/km]	Ø [mm]	Cu	G [kg]
052597	3X25 + 3X25/3	0.795	40.3	960	2380
052598	3X35 + 3X25/3	0.565	44.6	1248	2920
052599	3X50 + 3X25/3	0.393	47.7	1680	3520
053002	3X70 + 3X35/3	0.277	53.4	2352	4550
054490	3X95 + 3X50/3	0.21	59.6	3216	5730

URSUS[®] MT KN PLUS 8.7/15 kV

Nominal voltage U₀: 8.7 kV

Nominal voltage U: 15 kV

Maximum permitted operating voltage in 18 kV

three-phase systems:

Test voltage: 24 kV

part no.	part name	RI [Ohm/km]	Ø [mm]	Cu	G [kg]
052600	3X25 + 3X25/3	0.795	46.4	960	2860
052601	3X35 + 3X25/3	0.565	47.9	1248	3210
052602	3X50 + 3X25/3	0.393	51.2	1680	3830

URSUS[®] MT KN PLUS 12/20 kV

Nominal voltage U_o:	12 kV
Nominal voltage U:	20 kV
Maximum permitted operating voltage in three-phase systems:	24 kV
Test voltage:	29 kV

part no.	part name	RI [Ohm/km]	Ø [mm]	Cu	G [kg]
052603	3X25 + 3X25/3	0.795	48.1	960	3080
052590	3X35 + 3X25/3	0.565	52.3	1248	3460
052604	3X50 + 3X25/3	0.393	55.5	1680	4310
053383	3X240 + 3X120/3	0.0817	86.4	8064	12960

RI	Conductor resistance
Ø	outer diameter approx.
Cu	Copper weight (GER)
G	net weight per 1000