

# Coaxial cable

## FABER<sup>®</sup> VIDEO SDI/HD 0,6/2,8




DERZEIT KEIN BILD VERFÜGBAR. | NO IMAGE AVAILABLE.

**Application:** For connection of video components indoors. The cable may be used in HD-SDI interfaces.

### Construction and technical data:

**Permitted outer cable temperature, fixed, °C:** -5 - +70 °C



*The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.*

FABER<sup>®</sup> Video cables SDI/HD 0.6/2.8 75 ohm

<b>Colour of outer sheath:</b>	green
<b>inner conductor material:</b>	copper, solid, bare
<b>Inner conductor diameter, mm:</b>	0.6 mm
<b>Insulation:</b>	foam-PE
<b>Insulation diameter:</b>	2.8 mm
<b>Outer screen:</b>	aluminium foil + tinned copper braid
<b>Optical coverage:</b>	90 %
<b>Sheathing material:</b>	PVC
<b>Minimum bending radius:</b>	25 x Ø
<b>Operating temperature:</b>	-40 - +70 °C
<b>Impedance, ohm:</b>	75 Ohm
<b>DC-resistance inner conductor:</b>	63 Ohm/km
<b>DC-resistance outer screen:</b>	16 Ohm/km

part no.	part name	Ø [mm]	Cu	G [kg]
101207	0.6/2.8 GN	4.2	17	38

Ø | outer diameter approx.

Cu | Copper weight (GER)

G | net weight per 1000