

coupling for cable trays

type number: **KSBS 50** for width of cable tray 50 mm
 KSBS 75 for width of cable tray 75 mm
 KSBS 100 for width of cable tray 100 mm
 KSBS 150 for width of cable tray 150 mm
 KSBS 200 for width of cable tray 200 mm
 KSBS 300 for width of cable tray 300 mm

for height of cable tray: 60 mm

length: 200 mm

thickness of metal sheet: 1,5 mm

product description: This cable coupling is suitable for connecting cable trays to create cable trays with maintained functionality during fires.

For connecting there are designed bolts NSM 6X10 (width 50-150 mm - 16 pcs; width 200-300 mm - 24 pcs). To protect the cables, the bolt head is inside the cable tray.

A bolt with a GMT surface finish is used for a tray with an F surface finish.

configuration: PO - Pre-Galvanized, zinc-layer 15 - 27 µm
 POF - Hot Dip Galvanized, zinc-layer 50 - 100 µm

sales amount: á 1 pc

certification: EN 61537:02

classification: ZP 27/2008 P90-R
 DIN 41012-12 E90
 STN 92 0205 PS 90
 Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire
 Systems may be supplied with various surface finishes whereas the surface finish does not affect the determined maintained time of operability in fire.

storage: EN 60721-3-1

