

cable tray

type number:	KZ 60X50X1.50	width of cable tray 50 mm
	KZ 60X75X1.50	width of cable tray 75 mm
	KZ 60X100X1.50	width of cable tray 100 mm
	KZ 60X150X1.50	width of cable tray 150 mm
	KZ 60X200X1.50	width of cable tray 200 mm
	KZ 60X300X1.50	width of cable tray 300 mm
height of cable tray:	60 mm	
length of cable tray:	3000 mm	
thickness of metal sheet:	1,5 mm	



product description: Cable trays are usable for tray with maintained functionality in fire.
 Cable trays are classified for standard constructions.
 For connecting the trays there are designated the couplings KSBS.

configuration: PO - Pre-Galvanized, zinc-layer 15 - 27 µm
 POF - Hot Dip Galvanized, zinc-layer 50 - 100 µm

sales amount: à 3 m

certification: EN 61537:02

classification: ZP 27/2008 P90-R
 DIN 41012-12 E90
 STN 92 0205 PS 90
 Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire Systems may be supplied with various surface finishes whereas the surface finish does not affect the determined maintained time of operability in fire.

storage: EN 60721 3-1

