

reduction

type number	A	H	thickness of metal sheet
SR 35X25	26	25	1,0
SR 35X50	51	25	1,0
SR 35X75	76	25	1,0
SR 35X100	101	25	1,0
SR 35X125	126	25	1,0
SR 35X150	151	25	1,0
SR 35X200	201	25	1,0
SR 35X250	251	25	1,0
SR 35X300	301	25	1,0
SR 35X350	351	25	1,0
SR 35X400	401	25	1,0
SR 60X25	26	50	1,0
SR 60X50	51	50	1,0
SR 60X75	76	50	1,0
SR 60X100	101	50	1,0
SR 60X125	126	50	1,0
SR 60X150	151	50	1,0
SR 60X200	201	50	1,0
SR 60X250	251	50	1,0
SR 60X300	301	50	1,0
SR 60X350	351	50	1,0
SR 60X400	401	50	1,0
SR 85X25	26	75	1,0
SR 85X50	51	75	1,0
SR 85X75	76	75	1,0
SR 85X100	101	75	1,0
SR 85X125	126	75	1,0
SR 85X150	151	75	1,0
SR 85X200	201	75	1,0
SR 85X250	251	75	1,0
SR 85X300	301	75	1,0
SR 85X350	351	75	1,0
SR 85X400	401	75	1,0
SR 110X25	26	100	1,0
SR 110X50	51	100	1,0
SR 110X75	76	100	1,0
SR 110X100	101	100	1,0
SR 110X125	126	100	1,0
SR 110X150	151	100	1,0
SR 110X200	201	100	1,0
SR 110X250	251	100	1,0
SR 110X300	301	100	1,0
SR 110X350	351	100	1,0
SR 110X400	401	100	1,0

product description: The reduction is used to change the width of cable trays running through JUPITER cable trays or cable ladders.

To fix the connection use the bolt NSM 6X10. To protect the cables, the bolt head is inside the cable tray.

A bolt with a GMT surface finish is used for a tray with an F surface finish.

The reduction may be supplied in polyester varnish (varnish layer 60, 100 µm).

configuration: S - Pre-Galvanized, zinc-layer 15 - 27 µm
F - Hot Dip Galvanized, zinc-layer 50 - 100 µm
EC - epoxy coating for indoor environment, - total paint, 60 µm

sales amount: á 1 pc

certification: EN 61537:02

storage: EN 60721-3-1

