

## clamps DOBRMAN

item number	configuration	inner diameter (mm)	w eight 100 pcs (kg)	packing (pcs)
<b>5208 D</b>	ZNCR	8	1,11	50
<b>5210 D</b>	ZNCR	10	1,12	50
<b>5212 D</b>	ZNCR	12	1,15	50
<b>5216 D</b>	ZNCR	16	1,23	50
<b>5220 D</b>	ZNCR	20	1,33	50
<b>5225 D</b>	ZNCR	25	1,62	50
<b>5232 D</b>	ZNCR	32	1,79	50
<b>5240 D</b>	ZNCR	40	2,29	50
<b>5250 D</b>	ZNCR	50	2,92	25
<b>5263 D</b>	ZNCR	63	7,12	25



**product description:** DOBRMAN clamps are used to fasten cables to the base material to create cable trays with maintained functionality in the fire. The clamps are fixed to the base material using KPO 6 anchor or ZT 6 threaded rod and KPOZ 6 anchor. Max. fixing spacing is 600 mm. On the clamp there is the thread M6 for its fixing. To facilitate the installation, the clamp is provided with a groove for insertion; it is not necessary to separate completely the top part of the clamp during the installation.

**maximum load:** max. 3 cables into one clamp

**configuration:** ZNCR - galvanized steel

**sales amount:** á 1 pc

**classification:** ZP 27/2008, ČSN 73 0895 ..... P 90-R  
DIN 41012-12 ..... E 90  
STN 92 0205 ..... PS 90

The fire classification is dependent on the specific conditions of the cable tray, detailed in the catalogue Systems with maintained functionality in fire.

**storage:** EN 60721-3-1

