



product description: for position fixation of several pipes in one excavation  
 distance spacers are for fixation 8 pipes and spacer can be split for fixation 2, 4 and 6 pipes

thermal resistance: -45 - +60 °C

certification: EN 61386-24:11, EN 61386-1 ed.2:09

storage: ČSN 64 0090



item number	outer Ø pipe d (mm)	distance a (mm)	height b (mm)	fixing width h (mm)	fixing height k (mm)	material thickness tl. (mm)	total width l (8x) (mm)	total width after opening l (2x) (mm)	total width after opening l (4x) (mm)	total width after opening l (6x) (mm)
<b>07050/8_FB</b>	50	30	97	12	34	2,5	328	80	160	240
<b>07063/8_FB</b>	63	30	116	12	43	2,5	381	95	190	280
<b>07075/8_FB</b>	75	25	125	12	50	2,5	408	105	208	305
<b>07090/8_FB</b>	90	28	148	14	60	2,5	482	125	247	360
<b>07110/8_FB</b>	110	30	190	15	80	3	568	142	284	426
<b>07125/8_FB</b>	125	38	210	20	88	3	658	175	336	497
<b>07160/8_FB</b>	160	60	270	25	107	5	885	225	450	665
<b>07200/8_FB</b>	200	80	345	25	133	5	1135	287	575	847

