

## DATA SHEET

coupling for corrugated pipes KOPOFLEX and KOPODUR  
and doublecoated corrugated drainage pipes DUODREN



product description: slip-over coupling is intended to connect the corrugated pipes KOPOFLEX® or KOPODUR® and for connection of DUODREN drainage pipes  
when using a sealing ring, the protection class is IP67

material: PE

halogen-free: yes

self-snuffing: no

thermal resistance: -45 - +60 °C

fire class for underlying material: A1

UV stable: no

protection types: IP40

certification: EN 61386-24:11, EN 61386-1 ed.2:09

storage: ČSN 64 0090



chemical resistance: YES: aceton, amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate  
NO: anilin, chlorinated hydrocarbons, tetrachlorocarbon

| item number     | outer Ø<br>pipe<br>(mm) | for pipes                       |
|-----------------|-------------------------|---------------------------------|
| <b>02040_FA</b> | 40                      | KF 09040; KD 09040              |
| <b>02050_FA</b> | 50                      | KF 09050; KD 09050              |
| <b>02063_FA</b> | 63                      | KF 09063; KD 09063; DUODREN 63  |
| <b>02075_FA</b> | 75                      | KF 09075; KD 09075; DUODREN 75  |
| <b>02090_FA</b> | 90                      | KF 09090; KD 09090; DUODREN 90  |
| <b>02110_FA</b> | 110                     | KF 09110; KD 09110; DUODREN 110 |
| <b>02125_FA</b> | 125                     | KF 09125; KD 09125              |
| <b>02160_FA</b> | 160                     | KF 09160; KD 09160              |
| <b>02200_FA</b> | 200                     | KF 09200; KD 09200              |