



product description: connectors are designed to join rigid and flexible pipes  
 possibility to install in places with risk of flammable gases and vapor – danger zone 2  
 possibility to install in places with explosive risk of dust – danger zone 22

material: PVC  
 color: white RAL 9003, light gray RAL 7035, dark gray RAL 7012, black RAL 9005  
 self-snuffing: yes, within 30 s  
 temperature resistance: -25 - +60 °C  
 fire class for underlying material: A1-F  
 UV stable: no  
 mechanical protection according to EN 50102: IK09  
 certification: EN 61386-1 ed.2:09, EN 50102  
 storage: ČSN 64 0090



chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate  
 NO: aceton, benzen, phenol solution 5%, chlorinated hydrocarbons, tetrachlorocarbon

item number	dn pipe (mm)	L	weight (g/pc)	package (pcs)	colour	for pipes
<b>0216_FB</b>	16	45	7	10 / 1300	black RAL 9005	2316E
<b>0216_HB</b>	16	45	7	10 / 1300	white RAL 9003	1416E
<b>0216_KB</b>	16	45	7	10 / 1300	light grey RAL 7035	1216E
<b>0216_LB</b>	16	45	7	10 / 1300	dark grey RAL 7012	1516E 4016E 8016E
<b>0220_FB</b>	20	50	10	10 / 800	black RAL 9005	2320
<b>0220_HB</b>	20	50	10	10 / 800	white RAL 9003	1420
<b>0220_KB</b>	20	50	10	10 / 800	light grey RAL 7035	1220
<b>0220_LB</b>	20	50	10	10 / 800	dark grey RAL 7012	1520 4020 8020
<b>0225_FB</b>	25	60	16	10 / 480	black RAL 9005	2325
<b>0225_HB</b>	25	60	16	10 / 480	white RAL 9003	1425
<b>0225_KB</b>	25	60	16	10 / 480	light grey RAL 7035	1225
<b>0225_LB</b>	25	60	16	10 / 480	dark grey RAL 7012	1525 4025 8025
<b>0232_FB</b>	32	70	25	10 / 260	black RAL 9005	2332
<b>0232_HB</b>	32	70	25	10 / 260	white RAL 9003	1432
<b>0232_KB</b>	32	70	25	10 / 260	light grey RAL 7035	1232
<b>0232_LB</b>	32	70	25	10 / 260	dark grey RAL 7012	1532 4032 8032
<b>0240_FB</b>	40	80	39	10 / 120	black RAL 9005	2340
<b>0240_HB</b>	40	80	39	10 / 120	white RAL 9003	1440
<b>0240_KB</b>	40	80	39	10 / 120	light grey RAL 7035	1240
<b>0240_LB</b>	40	80	39	10 / 120	dark grey RAL 7012	1540 4040 8040
<b>0250_FB</b>	50	88	53	10 / 180	black RAL 9005	2350
<b>0250_HB</b>	50	88	53	10 / 180	white RAL 9003	1450
<b>0250_KB</b>	50	88	53	10 / 180	light grey RAL 7035	1250
<b>0250_LB</b>	50	88	53	10 / 180	dark grey RAL 7012	1550 4050 8050
<b>0263_FB</b>	63	105	86	2 / 50	black RAL 9005	1563
<b>0263_HB</b>	63	105	86	2 / 44	white RAL 9003	4063
<b>0263_KB</b>	63	105	86	2 / 44	light grey RAL 7035	8063
<b>0263_LB</b>	63	105	86	2 / 50	dark grey RAL 7012	