

item number			Ø outer	Ø inner	thread	length
configuration S	configuration F	configuration EOZ				
6013 ZNM	6013 ZN	6013	20,4	18,2	P13,5	3000
6016 ZNM	6016 ZN	6016	22,5	20,3	P16	3000
6021 ZNM	6021 ZN	6021	28,3	25,7	P21	3000
6029 ZNM	6029 ZN	6029	37	34,4	P29	3000
6036 ZNM	6036 ZN	6036	47	44	P36	3000
6042 ZNM	6042 ZN	6042	54	51	P42	3000



product description: Electrical wiring tubes are suitable for creating cable trays with maintained functionality during fires. They are installed horizontally on the wall or ceiling. OMEGA clamps are used to attach them to the base material, installed max. 1,200 mm apart. For connection of pipes it is necessary to order steel couplings 313/3 - 342/3, which replace the already supplied couplings, supplied with pipes. One cable may be installed into each electrical wiring tube; the cable diameter must not exceed the max. tube cross section used, i.e. 60%.

configuration: S - Pre-Galvanized, zinc-layer 15 - 27 µm
 F - Hot Dip Galvanized, zinc-layer 50 - 100 µm
 EOZ - powder coating, black color RAL 9005

sales amount: á 3000 mm

certification: EN 61 386-1 ed.2

classification: ZP 27/2008 P 90-R
 DIN 41012-12 E 90
 STN 92 0205 PS 90
 Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire. Systems may be supplied with various surface finishes whereas the surface finish does not affect the determined maintained time of operability in fire.

storage: EN 60721-3-1

