



product description: the bushings are designed to mechanically protect the conductors or cables coming from the steel pipe
plug the bushing from outside on the end of pipe before installing cables

material: PE

halogen-free: yes

color: gray

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

certification: EN 61386-1 ed.2:09, EN 61386-21:04

storage: ČSN 64 0090



chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
NO: aceton, benzen, phenol solution 5%, chlorinated hydrocarbons, tetrachlorocarbon

item number	di (mm)	dn outer Ø pipe (mm)	weight 1 pc (kg)	package (pcs)	for pipes
4813/P_KB	14,5	20,4	0,002	100 / 3000	6013..., 6213...
4816/P_KB	15,5	22,5	0,004	100 / 1200	6016..., 6216...
4821/P_KB	21,5	28,3	0,004	100 / 1000	6021..., 6221...
4829/P_KB	29,5	37	0,007	100 / 400	6029..., 6229...
4836/P_KB	37	47	0,010	100 / 300	6036..., 6236...
4842/P_KB	41,5	54	0,015	75 / 150	6042..., 6242...