



product description: the bushings are designed to mechanically protect the conductors or cables coming from the steel pipe
plug the bushing from outside on the end of pipe before installing cables

material: PE
 halogen-free: yes
 color: gray
 self-snuffing: yes, within 30 s
 temperature resistance: -5 - +60 °C
 certification: EN 61386-1 ed.2:09
 storage: ČSN 64 0090



chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
 NO: aceton, benzen, phenol solution 5%, chlorinated hydrocarbons, tetrachlorocarbon

item number	di (mm)	dn outer Ø (mm)	weight 1pc (kg)	package (pcs)	for pipes
4816E_KA	12	16	0,001	100 / 3000	6016E..., 6216E...
4820_KA	16	20	0,001	100 / 1200	6020..., 6220...
4825_KA	21	25	0,003	100 / 800	6025..., 6225...
4832_KA	28	32	0,005	50 / 400	6032..., 6232...
4840_KA	35	40	0,007	50 / 200	6040..., 6240...
4850_KA	43	50	0,012	25 / 100	6050..., 6250...
4863_KA	57	63	0,022	10 / 70	6063..., 6263...