



product description: for fixing pipes SPIROFLEX
conduit bushing provides protection IP64

material: PVC
 color: gray RAL 7035
 self-snuffing: yes, within 30 s
 temperature resistance: -5 - +60 °C
 fire class for underlying material: A1-F
 UV stable: no
 protection types: IP64
 certification: EN 61386-1 ed.2:09
 storage: ČSN 64 0090



chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
 NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

| item number | di pipe (mm) | for pipes | thread | weight (g/pc) | package (pcs) |
|-----------------|--------------|-----------|---------|---------------|---------------|
| SFM20_KB | 16 | SF16 | M20x1,5 | 11 | 25 |
| SFM25_KB | 20 | SF20 | M25x1,5 | 15 | 25 |
| SFM32_KB | 25 | SF25 | M32x1,5 | 26 | 10 |
| SFM40_KB | 32 | SF32 | M40x1,5 | 39 | 10 |